

CNF Encodings of Binary Constraint Trees (Extended Abstract)

Ruiwei Wang ✉

School of Computing, National University of Singapore

Roland H.C. Yap ✉

School of Computing, National University of Singapore

Abstract

Ordered Multi-valued Decision Diagrams (MDDs) have been shown to be useful to represent finite domain functions/relations. For example, various constraints can be modelled with MDD constraints. Recently, a new representation called Binary Constraint Tree (BCT), which is a (special) tree structure binary Constraint Satisfaction Problem, has been proposed to encode MDDs and shown to outperform existing MDD constraint propagators in Constraint Programming solvers. BCT is a compact representation, and it can be exponentially smaller than MDD for representing some constraints. Here, we also show that BCT is compact for representing non-deterministic finite state automaton (NFA) constraints. In this paper, we investigate how to encode BCT into CNF form, making it suitable for SAT solvers. We present and investigate five BCT CNF encodings. We compare the propagation strength of the BCT CNF encodings and experimentally evaluate the encodings on a range of existing benchmarks. We also compare with seven existing CNF encodings of MDD constraints. Experimental results show that the CNF encodings of BCT constraints can outperform those of MDD constraints on various benchmarks.

2012 ACM Subject Classification Computing methodologies → Artificial intelligence; Software and its engineering → Constraint and logic languages

Keywords and phrases BCT, CNF, MDD, NFA / MDD constraint, propagation strength

Digital Object Identifier 10.4230/LIPIcs.CP-DP.2022.20

1 Introduction

Ordered Multi-valued Decision Diagram (MDD) [14] is a compact representation which can be used to encode finite domain functions/relations. Many constraints can be encoded into compact MDD constraints, such as the regular constraints [12], table constraints [4], among and sequence constraints [9]. MDD constraints are also useful to model problems requiring specific constraints which are not readily modelled with existing known constraints [5]. In Constraint Programming (CP) solvers, MDD constraints can be directly handled with Generalized Arc Consistency (GAC) propagators. Alternatively, MDD constraints can also be solved by SAT solvers by encoding MDD constraints into CNF form [1]. In this way, SAT solvers can directly handle the constraints which can be modelled with MDDs constraints.

Binary constraint is also a general representation for constraints. Any non-binary constraint can be transformed into binary constraints through binary encodings such as dual encoding [6], hidden variable encoding [13], double encoding [15] and bipartite encoding [18]. Recently, binary encodings with specialized Arc Consistency (AC) propagators [17, 18] has been shown to outperform the GAC propagators of non-binary table constraints [20]. Similar to MDDs, the binary constraints can also be encoded into CNF with different CNF encodings, such as the log encoding [16], direct encoding [16] and support encoding [8].

Recently, a new representation called Binary Constraint Tree (BCT) [19], which is a set of binary constraints with tree structures (a special binary CSP), has been proposed to encode MDDs. BCT is a compact representation, and it can be exponentially smaller than MDD. In



© Ruiwei Wang and Roland H.C. Yap;
licensed under Creative Commons License CC-BY 4.0

The doctoral program of CP 2022.

Editor: Hélène Verhaeghe; Article No. 20; pp. 20:1–20:3



Leibniz International Proceedings in Informatics

Schloss Dagstuhl – Leibniz-Zentrum für Informatik, Dagstuhl Publishing, Germany

	Log	Direct	Minimal Support	Partial Support	Support
Weak consistency	✗	✗	✓	✓	✓
Domain consistency	✗	✗	✗	✓	✓
Unit refutation completeness	✗	✗	✓	✓	✓
Propagation completeness	✗	✗	✗	✗	✓

■ **Table 1** Strength of Unit Propagation on various encodings of BCT constraints. The label ✓(✗) denotes CNF encodings implement (does not implement) a certain unit propagation strength level.

45 this paper, we also show that non-deterministic finite state automaton (NFA) constraints
 46 [3] can be transformed into BCT constraints without exponential blow up but not MDD
 47 constraints. Furthermore, a GAC propagator of BCT constraints [19] has been shown to
 48 outperform the state-of-the-art MDD GAC propagators. The results in [19] show that BCT
 49 has great potential for encoding and reducing MDDs. In this work, we investigate how to
 50 encode BCT constraints into CNF instances and apply them in SAT solvers.

51 2 Main contributions

52 We investigate five CNF encodings of BCT constraints using the well-known log, direct,
 53 support encodings and our new encodings: partial support encoding and minimal support
 54 encoding. Then we analyze the strength of unit propagation on these five CNF encodings.
 55 We consider 4 propagation levels: weak consistency, domain consistency, unit refutation
 56 completeness [7, 1, 10, 11] and propagation completeness [2, 1, 10, 11], where propagation
 57 completeness is the strongest level, unit refutation completeness is incomparable with domain
 58 consistency, and weak consistency is the weakest level.

59 Table 1 summarizes the strength of unit propagation on all five CNF encoding of BCT
 60 constraints. The support encoding of BCT constraints, which implements propagation
 61 completeness, can have a greater propagation strength than the other CNF encodings. The
 62 partial support encoding and minimal support encoding are more compact than the support
 63 encoding but their propagation strength is weaker than the support encoding. The partial
 64 support encoding implementing domain consistency is stronger than the log, direct and
 65 minimal support encodings. In addition, the log and direct encodings of BCT constraints
 66 are weaker than the minimal support encoding, since the log and direct encodings of BCT
 67 constraints do not implement weak consistency.

68 We evaluate our five CNF encodings of BCT constraints with seven existing CNF
 69 encodings [1] of MDD constraints and also a BCT GAC propagator [19] on a range of existing
 70 benchmarks. Our experimental results show that the CNF encodings of BCT constraints can
 71 outperform those of MDD constraints. Our results show that solving of BCT constraints as
 72 well as NFA/MDD constraints is promising on SAT solvers. While there is some initialization
 73 and encoding time for all methods, this is overall less significant than the solving time. The
 74 initialization time becomes significant when the encoding becomes large. For example, on
 75 some instances, the encoding cost becomes significant in the MDD CNF encodings with
 76 some being memory-out. BCT CNF encodings generally outperform MDD CNF encodings.
 77 As with the MDD CNF encoding experiments in [1] where they found performance was
 78 mixed between CNF encodings and their propagator comparison, we also find that for some
 79 problems the BCT CNF encoding is the best while for other problems the BCT propagator
 80 in Abscon is the best. BCT CNF encoding is overall competitive or best for many instances
 81 and increases the flexibility and choices in solving of BCT (and NFA/MDD) constraints.

References

- 1 Ignasi Abío, Graeme Gange, Valentin Mayer-Eichberger, and Peter J Stuckey. On CNF encodings of decision diagrams. In *International Conference on AI and OR Techniques in Constraint Programming for Combinatorial Optimization Problems*, pages 1–17. Springer, 2016.
- 2 Lucas Bordeaux and Joao Marques-Silva. Knowledge compilation with empowerment. In *International Conference on Current Trends in Theory and Practice of Computer Science*, pages 612–624. Springer, 2012.
- 3 Kenil C.K. Cheng, Wei Xia, and Roland H.C. Yap. Space-time tradeoffs for the regular constraint. In *International Conference on Principles and Practice of Constraint Programming*, pages 223–237. Springer, 2012.
- 4 Kenil C.K. Cheng and Roland H. C. Yap. An MDD-based generalized arc consistency algorithm for positive and negative table constraints and some global constraints. *Constraints*, 15(2):265–304, 2010.
- 5 Kenil C.K. Cheng and Roland H.C. Yap. Applying ad-hoc global constraints with the case constraint to still-life. *Constraints*, 11(2-3):91–114, 2006.
- 6 Rina Dechter and Judea Pearl. Tree clustering for constraint networks. *Artificial Intelligence*, 38(3):353–366, 1989.
- 7 Alvaro Del Val. Tractable databases: How to make propositional unit resolution complete through compilation. In *International Conference on Principles of Knowledge Representation and Reasoning*, pages 551–561. Elsevier, 1994.
- 8 Ian P Gent. Arc consistency in SAT. In *European Conference on Artificial Intelligence*, pages 121–125, 2002.
- 9 Willem-Jan van Hoeve, Gilles Pesant, Louis-Martin Rousseau, and Ashish Sabharwal. Re-visiting the sequence constraint. In *International conference on principles and practice of constraint programming*, pages 620–634. Springer, 2006.
- 10 Petr Kučera and Petr Savický. Propagation complete encodings of smooth DNNF theories. *CoRR*, abs/1909.06673, 2019.
- 11 Petr Kučera and Petr Savický. Bounds on the size of PC and URC formulas. *Journal of Artificial Intelligence Research*, 69:1395–1420, 2020.
- 12 Gilles Pesant. A regular language membership constraint for finite sequences of variables. In *International conference on principles and practice of constraint programming*, pages 482–495. Springer, 2004.
- 13 Francesca Rossi, Charles J. Petrie, and Vasant Dhar. On the equivalence of constraint satisfaction problems. In *European Conference on Artificial Intelligence*, pages 550–556, 1990.
- 14 Arvind Srinivasan, Timothy Ham, Sharad Malik, and Robert K Brayton. Algorithms for discrete function manipulation. In *IEEE/ACM International Conference on Computer-Aided Design*, pages 92–95, 1990.
- 15 Kostas Stergiou and Toby Walsh. Encodings of non-binary constraint satisfaction problems. In *AAAI Conference on Artificial Intelligence*, pages 163–168, 1999.
- 16 Toby Walsh. SAT v CSP. In *International Conference on Principles and Practice of Constraint Programming*, pages 441–456, 2000.
- 17 Ruiwei Wang and Roland H. C. Yap. Arc consistency revisited. In *International Conference on Integration of Constraint Programming, Artificial Intelligence, and Operations Research*, pages 599–615, 2019.
- 18 Ruiwei Wang and Roland H. C. Yap. Bipartite encoding: A new binary encoding for solving non-binary cps. In *International Joint Conference on Artificial Intelligence*, pages 1184–1191, 2020.
- 19 Ruiwei Wang and Roland H. C. Yap. Encoding multi-valued decision diagram constraints as binary constraint trees. In *AAAI Conference on Artificial Intelligence*, 2022.
- 20 Roland H. C. Yap, Wei Xia, and Ruiwei Wang. Generalized arc consistency algorithms for table constraints: A summary of algorithmic ideas. In *AAAI Conference on Artificial Intelligence*, pages 13590–13597, 2020.